

## TECHNICAL DATA SHEET

# Fortis F1 Industrial Spray Adhesive

ISSUED: February 2015

## INTRODUCTION

### Fortis F1 Industrial Spray Adhesive

Is a fast-drying, industrial spray adhesive that bonds to most substrates.

## USE

### Fortis F1 Industrial Spray Adhesive

Provides fast, strong adhesion to most substrates including concrete, wood, MDF, laminates, Fabric, Felt, Cork & Fibrous Glass, Flexible Foam (Latex, Urethane), Rigid Foam (Urethane), Leather, Rubber (Except EPDM), EPDM Rubber, Metal, Plastics (ABS, PVC, Acrylic), Plastics (High Performance Nylon), Glass & Ceramics, Paper & Cardboard, Plastics (Polyolefins and Thermoplastic Elastomers), Wood & Hardboard, Plastics (Flexible Vinyl).

## FEATURES

### Fortis F1 Industrial Spray Adhesive

- Strong and fast adhesion
- Excellent resistance to mildew and heat
- Interior/exterior use
- Retains elasticity, allowing for flexible adhesive sealing
- Water resistant
- Direct spray action

## TECHNICAL DATA

Application Temperature	> -5°C & < 55°C
Propellant	Hydrocarbon
Pack Size	500mL aerosol can
Shelf Life	12 months unopened, store in cool, dry conditions. DO NOT store below 10°C or over 50°C

## APPLICATION

### APPLICATION

- Shake well before use
- Due to the many variables and factors beyond the control of Fortis Adhesives & Coatings, and within the control & knowledge of the end user associated with use of such an adhesive product, it is strongly recommend that users trial this product with a small test sample prior to use on the intended project area. The user can then make a final assessment of the compatibility of this product for a given project.
- Spray only one surface of the two to be bonded
- Wait 30 seconds to 5 minutes after spraying then press surfaces together.
- Ensure adhesive is still moist
- Operating temperatures from -5°C up to +55°C.

### STORAGE AND DISPOSAL

- Pressurised dispenser – keep in cool place
- PROTECT FROM HEAT AND SUNLIGHT
- DO NOT EXPOSE CAN TO TEMPERATURES EXCEEDING 50°C. Such temperatures may occur in cars, or near heaters, stoves or open flames.
- KEEP AWAY FROM SOURCES OF IGNITION – NO SMOKING
- DO NOT store near naked flame, heat or incandescent material.
- DO NOT PEIRCE OR BURN THIS CAN EVEN WHEN EMPTY
- Aerosols should be completely empty before disposing

# TECHNICAL DATA SHEET

---

## SAFETY

- KEEP OUT OF REACH FROM CHILDREN
- EXTREEMLY FLAMMABLE
- DO NOT spray directly on humans or pets
- DO NOT spray on or near naked flame, pilot light, heat or incandescent material
- Toxic to aquatic life, do not throw product into water ways
- Avoid contact with eyes and skin and avoid breathing the vapour or spray mist.
- Store, store in cool, dry conditions, out of direct sunlight and in a well ventilated area. DO NOT store below 10°C or over 50°C.
- Good industrial hygiene should be observed at all times – Appropriate PPE should be worn including impervious gloves & eye wear.

### First Aid

**Eyes:** If sprayed into eyes, flush with water for 15min. Seek medical advice.

**Skin:** Wash affected area with soap and water.

**Inhalation:** If mists are inhaled, remove patient to fresh air. Seek medical advice.

**Swallowed:** Do NOT induce vomiting. Give milk or water to dilute. Seek medical advice.

For further information, refer to the Fortis Material Safety Data Sheet. [www.fortisadhesives.com.au](http://www.fortisadhesives.com.au)

### Disclaimer

*Fortis products should be used in accordance with the information contained here. Each user should read and consider this information carefully in the context of how the products will be handled and used in the workplace including in conjunction with other products. While the information contained here is to the best of our knowledge at the date of publication, Fortis makes no representation about the accuracy of the information. If you need clarification or more information, you should contact Fortis Adhesives & Coatings office directly. Fortis products are sold without express or implied warranties, other than as provided by statute, and subject to our standard terms and conditions (provided to customers and available on request). Subject to our standard terms and conditions, and any statutory provisions, Fortis accepts no responsibility (including in negligence) for loss or damage of any nature resulting from the use of Fortis Adhesives & Coatings products or reliance upon the information contained here*