



## SAFETY DATA SHEET

PRODUCT NAME **CONCRETE SHIELD ENHANCER PREMIUM**

### 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

**Supplier name** FORTIS ADHESIVES & COATINGS  
**Address** 177 – 179 Ordish Rd, Dandenong South, VIC, 3175, AUSTRALIA  
**Telephone** 03 9706 5448  
**Emergency** 13 11 26  
**Web site** [www.fortisadhesives.com.au](http://www.fortisadhesives.com.au)  
**Synonym(s)** ENHANCER PREMIUM  
**Use(s)** CONCRETE SEALANT • SEALANT  
**SDS date** 08 October 2015

### 2. HAZARDS IDENTIFICATION

CLASSIFIED AS HAZARDOUS ACCORDING TO SAFE WORK AUSTRALIA CRITERIA

**Risk Phrases**

R65 Harmful: May cause lung damage if swallowed.

**Safety Phrases**

S1/2 Keep locked up and out of reach of children.

S16 Keep away from sources of ignition - No smoking.

NOT CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE

<b>UN Number</b>	None Allocated	<b>Transport Hazard Class</b>	None Allocated
<b>Packing Group</b>	None Allocated	<b>Hazchem Code</b>	None Allocated

### 3. COMPOSITION/ INFORMATION ON INGREDIENTS

Ingredient	CAS Number	EC Number	Content
NAPHTHA (PETROLEUM), HYDROTREATED HEAVY	64742-48-9	265-150-3	Remainder
OCTAMETHYLCYCLOTETRASILOXANE	556-67-2	209-136-7	<5%
METHANOL	67-56-1	200-659-6	<1%
FLUORINATED POLYMERS	-	-	25%
METHYLTRIMETHOXYSILANE	1185-55-3	214-685-0	<10%
TETRABUTYL TITANATE	5593-70-4	227-006-8	<10%
TRIETHOXYOCTYLSILANE	2943-75-1	220-941-2	<10%

### 4. FIRST AID MEASURES

**Eye** If in eyes, hold eyelids apart and flush continuously with running water. Continue flushing until advised to stop by a Poisons Information Centre, a doctor, or for at least 15 minutes.

**Inhalation** If inhaled, remove from contaminated area. Apply artificial respiration if not breathing.

**Skin** If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. Continue flushing with water until advised to stop by a Poisons Information Centre or a doctor.

**Ingestion** For advice, contact a Poison Information Centre on 13 11 26 (Australia Wide) or a doctor (at once). If swallowed, do not induce vomiting.

**Advice to doctor** Treat symptomatically.

## 5. FIRE FIGHTING MEASURES

<b>Flammability</b>	Combustible. May evolve toxic gases (carbon/ silicon oxides, hydrocarbons) when heated to decomposition.
<b>Fire and explosion</b>	Evacuate area and contact emergency services. Toxic gases may be evolved in a fire situation. Remain upwind and notify those downwind of hazard. Wear full protective equipment including Self Contained Breathing Apparatus (SCBA) when combating fire. Use waterfog to cool intact containers and nearby storage areas.
<b>Extinguishing</b>	Dry agent, carbon dioxide or water fog. Prevent contamination of drains and waterways.
<b>Hazchem code</b>	None allocated.

## 6. ACCIDENTAL RELEASE MEASURES

<b>Personal precautions</b>	Wear Personal Protective Equipment (PPE) as detailed in section 8 of the SDS.
<b>Environmental precautions</b>	Prevent product from entering drains and waterways.
<b>Methods of cleaning up</b>	Contain spillage, then cover / absorb spill with non-combustible absorbent material (vermiculite, sand, or similar), collect and place in suitable containers for disposal.
<b>References</b>	See Sections 8 and 13 for exposure controls and disposal.

## 7. STORAGE AND HANDLING

<b>Storage</b>	Store in a cool, dry, well ventilated area, removed from incompatible substances, heat or ignition sources and foodstuffs. Ensure containers are adequately labelled, protected from physical damage and sealed when not in use. Check regularly for leaks or spills. Large storage areas should have appropriate fire protection systems. Store as a Class C1 Combustible Liquid (AS1940).
<b>Handling</b>	Before use carefully read the product label. Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking and smoking in contaminated areas.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### Exposure standards

Ingredient	Reference	TWA		STEL	
		ppm	mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>
Fluorides (as F)	SWA (AUS)	--	2.5	--	--
Methanol	SWA (AUS)	200	262	250	328
Mineral Oil Mist	SWA (AUS)	--	5	--	--

### Biological limits

Ingredient	Determinant	Sampling Time	BEI
METHANOL	Methanol in urine	End of shift	15 mg/L

Reference: ACGIH Biological Exposure Indices

<b>Engineering controls</b>	Avoid inhalation. Use in well ventilated areas. Where an inhalation risk exists, mechanical extraction ventilation is recommended. Maintain vapour levels below the recommended exposure standard.
-----------------------------	--

**PRODUCT NAME CONCRETE SHIELD ENHANCER PREMIUM****PPE**

<b>Eye / Face</b>	Wear splash-proof goggles.
<b>Hands</b>	Wear PVC or rubber gloves. When using large quantities or where heavy contamination is likely, wear viton (R) gloves.
<b>Body</b>	When using large quantities or where heavy contamination is likely, wear coveralls.
<b>Respiratory</b>	Where an inhalation risk exists, wear a Type A (Organic vapour) respirator.



---

**9. PHYSICAL AND CHEMICAL PROPERTIES**

---

<b>Appearance</b>	LIQUID
<b>Odour</b>	SLIGHT ODOUR
<b>Flammability</b>	CLASS C1 COMBUSTIBLE
<b>Flash point</b>	64°C
<b>Boiling point</b>	NOT AVAILABLE
<b>Melting point</b>	NOT AVAILABLE
<b>Evaporation rate</b>	NOT AVAILABLE
<b>pH</b>	NOT AVAILABLE
<b>Vapour density</b>	NOT AVAILABLE
<b>Specific gravity</b>	NOT AVAILABLE
<b>Solubility (water)</b>	NOT AVAILABLE
<b>Vapour pressure</b>	NOT AVAILABLE
<b>Upper explosion limit</b>	NOT RELEVANT
<b>Lower explosion limit</b>	NOT RELEVANT
<b>Partition coefficient</b>	NOT AVAILABLE
<b>Autoignition temperature</b>	NOT AVAILABLE
<b>Decomposition temperature</b>	NOT AVAILABLE
<b>Viscosity</b>	NOT AVAILABLE
<b>Explosive properties</b>	NOT AVAILABLE
<b>Oxidising properties</b>	NOT AVAILABLE
<b>Odour threshold</b>	NOT AVAILABLE

---

**10. STABILITY AND REACTIVITY**

---

<b>Chemical stability</b>	Stable under recommended conditions of storage.
<b>Conditions to avoid</b>	Avoid heat, sparks, open flames and other ignition sources. Avoid exposure to moisture.
<b>Material to avoid</b>	Incompatible with oxidising agents (e.g. hypochlorites), acids (e.g. nitric acid), alkalis (e.g. sodium hydroxide), heat and ignition sources.
<b>Hazardous Decomposition Products</b>	May evolve toxic gases (carbon/ silicon oxides, hydrocarbons) when heated to decomposition.
<b>Hazardous Reactions</b>	Hazardous polymerization is not expected to occur.

---

**11. TOXICOLOGICAL INFORMATION**

---

<b>Health Hazard Summary</b>	May be harmful - irritant. During the curing process, small amounts of methanol vapour are evolved. This may only present a hazard in poorly ventilated areas. Use safe work practices to avoid eye or skin contact and inhalation. Due to the product form and nature of use, the potential for adverse health effects may be reduced. The cured product is considered non toxic.
<b>Eye</b>	Irritant. Contact may result in irritation, lacrimation, pain and redness.
<b>Inhalation</b>	Irritant. Over exposure to vapours may result in irritation of the nose and throat, coughing, nausea and headache.
<b>Skin</b>	Irritant. Contact may result in drying and defatting of the skin, rash and dermatitis.
<b>Ingestion</b>	May be harmful. Ingestion may result in gastrointestinal irritation, nausea and vomiting. However, due to product form ingestion is considered unlikely.
<b>Toxicity data</b>	

**PRODUCT NAME CONCRETE SHIELD ENHANCER PREMIUM**

OCTAMETHYLCYCLOTETRASILOXANE (556-67-2)	
LD50 (oral)	1540 mg/kg (rat)
LD50 (dermal)	1770 mg/kg (rat)
METHANOL (67-56-1)	
LD50 (oral)	300 mg/kg (human)
LD50 (dermal)	15,800 mg/kg (rabbit)
LC50 (inhalation)	50 g/m <sup>3</sup> /2 hours (mouse)
METHYLTRIMETHOXYSILANE (1185-55-3)	
LD50 (oral)	12500 uL/kg (rat)
TETRABUTYL TITANATE (5593-70-4)	
LD50 (oral)	3122 mg/kg (rat)
TRIETHOXYOCTYLSILANE (2943-75-1)	
LD50 (oral)	100.6 mL/kg (rat)
LD50 (dermal)	5.91 mL/kg (rabbit)

**12. ECOLOGICAL INFORMATION**

<b>Toxicity</b>	No information provided.
<b>Persistence and degradability</b>	No information provided.
<b>Bioaccumulative potential</b>	No information provided.
<b>Mobility in soil</b>	No information provided.
<b>Other adverse effects</b>	No information provided.

**13. DISPOSAL CONSIDERATIONS**

<b>Waste disposal</b>	For small amounts, absorb with sand, vermiculite or similar and dispose of to an approved landfill site. For large quantities, contact the manufacturer/supplier for additional information. Prevent contamination of drains and waterways as aquatic life may be threatened and environmental damage may result.
<b>Legislation</b>	Dispose of in accordance with relevant local legislation.

**14. TRANSPORT INFORMATION****NOT CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE, IMDG OR IATA**

	<b>LAND TRANSPORT (ADG)</b>	<b>SEA TRANSPORT (IMDG / IMO)</b>	<b>AIR TRANSPORT (IATA / ICAO)</b>
<b>UN Number</b>	None Allocated	None Allocated	None Allocated
<b>Proper Shipping Name</b>	None Allocated	None Allocated	None Allocated
<b>Transport Hazard Class</b>	None Allocated	None Allocated	None Allocated
<b>Packing Group</b>	None Allocated	None Allocated	None Allocated

**Environmental hazards** No information provided

**Special precautions for user**

**Hazchem code** None Allocated

**15. REGULATORY INFORMATION**

**Poison schedule** A poison schedule number has not been allocated to this product using the criteria in the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).

**Inventory Listing(s)** **AUSTRALIA: AICS (Australian Inventory of Chemical Substances)**  
All components are listed on AICS, or are exempt.

## 16. OTHER INFORMATION

### Additional information

**SILICONE SEALANTS:** Toxic vapours released upon curing may result in eye and respiratory tract irritation. A hazard exists when high concentrations are generated in poorly ventilated areas. Once curing is complete, irritating or toxic vapours should no longer be evolved and therefore an inhalation hazard is no longer anticipated. In this cured state the sealant is considered inert and relatively non toxic.

**RESPIRATORS:** In general the use of respirators should be limited and engineering controls employed to avoid exposure. If respiratory equipment must be worn ensure correct respirator selection and training is undertaken. Remember that some respirators may be extremely uncomfortable when used for long periods. The use of air powered or air supplied respirators should be considered where prolonged or repeated use is necessary.

### PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:

The recommendation for protective equipment contained within this report is provided as a guide only. Factors such as method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

### HEALTH EFFECTS FROM EXPOSURE:

It should be noted that the effects from exposure to this product will depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a ChemAlert report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

### Abbreviations

ACGIH	American Conference of Governmental Industrial Hygienists
CAS #	Chemical Abstract Service number - used to uniquely identify chemical compounds
CNS	Central Nervous System
EC No.	EC No - European Community Number
EMS	Emergency Schedules (Emergency Procedures for Ships Carrying Dangerous Goods)
GHS	Globally Harmonized System
GTEPG	Group Text Emergency Procedure Guide
IARC	International Agency for Research on Cancer
LC50	Lethal Concentration, 50% / Median Lethal Concentration
LD50	Lethal Dose, 50% / Median Lethal Dose
mg/m <sup>3</sup>	Milligrams per Cubic Metre
OEL	Occupational Exposure Limit
pH	relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline).
ppm	Parts Per Million
STEL	Short-Term Exposure Limit
STOT-RE	Specific target organ toxicity (repeated exposure)
STOT-SE	Specific target organ toxicity (single exposure)
SUSMP	Standard for the Uniform Scheduling of Medicines and Poisons
SWA	Safe Work Australia
TLV	Threshold Limit Value
TWA	Time Weighted Average

### Report status

This document has been compiled by RMT on behalf of the manufacturer, importer or supplier of the product and serves as their Safety Data Sheet ('SDS').

It is based on information concerning the product which has been provided to RMT by the manufacturer, importer or supplier or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer, importer or supplier.

While RMT has taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS.

**PRODUCT NAME    CONCRETE SHIELD ENHANCER PREMIUM**

**Prepared by**

Risk Management Technologies  
5 Ventnor Ave, West Perth  
Western Australia 6005  
Phone: +61 8 9322 1711  
Fax: +61 8 9322 1794  
Email: [info@rmt.com.au](mailto:info@rmt.com.au)  
Web: [www.rmt.com.au](http://www.rmt.com.au).

**[ End of SDS ]**